



# TYPE 61B 0,64/1,1kV

SANS 1520-1

# POWERMITE

Flexible copper screened mining cables



## CONSTRUCTION

<b>Cable type</b>	Type 61B 0.64/1.1 kV
<b>Conductors</b>	Flexible class 5 comply to SANS 1411 - 1 from tinned annealed copper wires left lay with semi-conducting rubber screen .
<b>Insulation</b>	Ethylene propylene thermosetting compound type RD 3 comply to SANS 1411-3 and a strippable semi-conducting core screen (triple extruded)
<b>Core of cable</b>	Three tinned copper braided screened power cores and three unscreened pilot cores one in each interstice laid up in the right hand lay around semi-conductive rubber filler.
<b>Inner sheath</b>	Poly-chloroprene thermosetting compound type RS 6 comply to SANS 1411-3 .
<b>Re-enforcement</b>	An open nylon braid . Minimum 16 of nylon strings .
<b>Outer sheath</b>	Poly-chloroprene thermosetting compound type RS 6 comply to SANS 1411-3 .
<b>Colour of sheath</b>	Black .
<b>Tests</b>	SANS 1520-1.
<b>Marking</b>	TF KABLE 3 Texoprene TR 61B (Size) (Voltage) CR SANS 1520-1 (Year)+metre marking

## FEATURES

- Excellent flexibility
- Water resistant and flame retardant
- Operating temperature min. ambient temp . -25 °C , max. conductor temp. 90°C.
- UV ,sunlight , ozone ,oil, resistant
- Embossing marking as per order.

## APPLICATIONS

# TYPE 61B 0,64/1,1kV

SANS 1520-1



- Electrically driven machines , movable electric apparatus in hazardous areas .Not for reeling purposes.
- Other industrial applications .

**Standard length cable packing** : 500m on drums. Other forms of packing and delivery are available on request

Table 1

Physical Properties							
<b>Power cores</b>							
Conductor sizes	(mm <sup>2</sup> )	35	50	70	95	120	150
Maximum wire diameter	( mm)	0.41	0.41	0.51	0.51	0.51	0.51
Approx. conductor diameter	( mm)	8.5	10.3	11.9	13.5	15.5	17.3
Maximum screen wire diameter	(mm)	0.31	0.31	0.31	0.31	0.31	0.31
Braided screen filling factor	(%)	80	80	80	80	80	80
Approx. summarized screen cross-section for power cores (weighing method)	(mm <sup>2</sup> )	27	32	37	43	47	52
<b>Pilot cores</b>							
Conductor sizes	( mm <sup>2</sup> )	6	6	16	16	16	16
Maximum wire diameter	( mm)	0.31	0.31	0.41	0.41	0.41	0.41
Approx. conductor diameter	( mm)	3.2	3.2	5.2	5.2	5.2	5.2
<b>Lay Ratio</b> (maximum)	(x PCD)	12	12	12	12	12	12
<b>Cable diameter</b>							
Approx.	(mm)	41	42.5	48	52.3	58	63.5
<b>Cable mass</b> (approx.)	(kg/m)	3.1	3.6	4.8	5.7	7.1	8.5
<b>Minimum bending radius</b>	(mm)	300	340	390	430	460	500
Maximum recommended tension	(kN)	1.6	2.3	3.2	4.3	5.4	6.8

# TYPE 61B 0,64/1,1kV

SANS 1520-1

# POWERMITE

Table 2

Electrical Properties						
<b>Power cores</b>						
Maximum cond. DC resistance @ 20 <sup>0</sup> C (Ω/km)	0.576	0.401	0.283	0.214	0.167	0.135
Maximum cond. DC resistance @ 90 <sup>0</sup> C (Ω/km)	0.734	0.511	0.360	0.273	0.213	0.171
Reactance (Ω/km)	0.090	0.090	0.088	0.086	0.086	0.085
Impedance (Z) @ 90 <sup>0</sup> C (Ω/km)	0.740	0.519	0.371	0.287	0.230	0.191
<b>Sustained current rating @ 30<sup>0</sup>C ambient</b>						
Laid out straight (A)	160	200	245	295	345	390
<b>Short circuit rating :</b>						
Symmetrical fault current (kA for 1 sec)	4.3	6.1	8.5	11.6	14.6	18.3
Earth fault current (screens) (kA for 1 sec)	2.1	3.1	3.5	4.1	4.1	4.1

All the information contained in this document - including tables and diagrams - is given in good faith and believed to be correct at the time of publication. The information does not constitute a warranty nor representation for which POWERMITE assumes legal responsibility. POWERMITE reserves rights to introduce changes to the document at any time.