




PC 01 + 03 + 05

16/32A SPLASHPROOF HIGH FREQUENCY PLUGS AND SOCKETS IP44 > 300zH 50 > 500V > MOULDED


PLUGS



A	Poles	Cat No.
16	3	2168
	4	A0143
	5	2189
32	3	2195
	4	266
	5	2244

	Current								
	16			32					
Poles	3	4	5	3	4	5			
Dimensions (mm)	a	45	169	169	213	213	214		
b	52	59	67	71	71	77			
h	59	66	73	83	83	90			
m	106	116	116	141	141	141			
n	108	132	132	168	168	168			
y	14	16,5	16,5	24	24	24			
z	6	7,5	7,5	7	7	7			
min. Cond. cross section	mm	1	1	2,5	2,5	2,5			
max. dhd. cross section	mm	2,5	2,5	2,5	6	6			


COUPLER



A	Poles	Cat No.
16	3	2441
	4	A0530
	5	2193
32	3	2196
	4	528
	5	2245

	Current								
	16			32					
Poles	3	4	5	3	4	5			
Dimensions (mm)	a	55	177	177	225	225	225		
b	51	58	66	66	66	73			
h	69	77	85	88	88	95			
y	14	17,5	17,5	24	24	24			
z	6	7,5	7,5	10	10	10			
min. Cond. cross section	mm	1	1	2,5	2,5	2,5			
max. dhd. cross section	mm	2,5	2,5	2,5	6	6			


WALL SOCKETS



A	Poles	Cat No.
16	3	586
	4	A0222
	5	3046
32	3	3139
	4	1427
	5	3154

	Current								
	16			32					
Poles	3	4	5	3	4	5			
Dimensions (mm)	a	28	128	128	128	128			
b	84	84	84	84	84	84			
c	120	122	124	136	136	138			
d	11	11	11	11	11	11			
e	68	68	68	68	68	68			
f	5,3	5,3	5,3	5,3	5,3	5,3			
g	4	4	4	4	4	4			
h	146	144	145	158	158	160			
M	25	25	25	32	32	32			
M*	2x M25 (blind)			2x M25 (blind)					
	to be cut out			to be cut out					
min. Cond. cross section	mm	4	1,5	2,5	2,5	2,5			
max. dhd. cross section	mm	4	4	10	10	10			
max. cable dia. in	mm	8	18	18	18/25	18/25			

BUILT-IN



A	Poles	Cat No.
16	3	3186
	4	1469
	5	3189
32	3	3201
	4	1486
	5	3192

	Current								
	16			32					
Poles	3	4	5	3	4	5			
Dimensions (mm)	a	3,5	100	100	100	100			
b	64	92	92	92	92	92			
c	50	56	56	60	60	60			
d	60	85	85	85	85	85			
e	52	77	77	77	77	77			
f	5,3	5,3	5,3	5,3	5,3	5,3			
g	7	8	8	8	8	8			
h	86	105	105	107	107	112			
hl	1	>	>	>	>	>			
k	42	31	32	52	52	53			
l	52	60	65	70	70	73			
ll	60	65	72	82	82	85			
a	20"	20"	20"	20"	20"	20"			
min. Cond. cross section	mm	5	1,5	2,5	2,5	2,5			
max. dhd. cross section	mm	4	4	10	10	10			

Note: All A numbers represent ex stock items. All other numbers are available on request. Other models like watertight IP67 plugs and sockets are also available on request.