


# 16/32A SPLASHPROOF PLUGS AND SOCKETS, IP44 LOW VOLTAGE 20 > 50V > MOULDED

## PLUGS

Current	16		32	
	5	3	4	5
Dimensions (mm)	a186	186	186	186
b	50	50	50	50
h	64	64	64	64
m	113	113	113	113
n	163	163	163	163
y	24	24	24	24
z	7	7	7	7
min. Cond. cross section mm	4		4	4
max. dhd. cross section mm	10		2x6	10


A	Poles	Cat No.
16	2	A0124
	3	A0125
32	2	642
	3	649



## COUPLERS

Current	16		32	
	5	3	4	5
Dimensions (mm)	a200	200	200	200
b	50	50	50	50
h	70	70	70	70
y	24	24	24	24
z	7	7	7	7
min. Cond. cross section mm	4		4	4
max. dhd. cross section mm	10		2x6	10


A	Poles	Cat No.
16	2	681
	3	A0517
32	2	694
	3	701



## WALL SOCKET OUTLET

Current	16		32	
	5	3	4	5
Dimensions (mm)	a126	126	126	126
b	83	83	83	83
c	115	115	115	115
d	11	11	11	11
e	68	68	68	68
f	5,3	5,3	5,3	5,3
g	4	4	4	4
h	146	146	146	146
Pg	21	21	21	21
Pg*	for 2x Pg 21 blind to be cut out		for 2x Pg 21 blind to be cut out	
min. Cond. cross section mm	4		4	4
max. Cond. cross section mm	10		2x6	10
max. cable dia. in mm	20,5	20,5	20,5	20,5


A	Poles	Cat No.
16	2	577
	3	584
32	2	590
	3	597



## BUILT-IN

Current	16		32	
	5	3	4	5
Dimensions (mm)	a 55	55	55	55
b	55	55	55	55
c	40	40	40	40
d	45	45	45	45
e	45	45	45	45
f	4,2	4,2	4,2	4,2
g	4	4	4	4
h	67	67	67	67
k	25	25	25	25
l	34	34	34	34
min. Cond. cross section mm	4		4	4
max. dhd. cross section mm	10		2x6	10

A	Poles	Cat No.
16	2	A0316
	3	A0317
32	2	616
	3	623



Note: All A numbers represent ex stock items. All other numbers are available on request. Other models like watertight IP67 and 50V plugs and sockets are available on request.