


IP67   WATERTIGHT, DISCONNECTOR WALL MOUNTED APPLIANCE INLET -

A	V	⊕ 2P+E	⊕ 3P+E	⊕ 3P+N+E
16	24	3PS1WA+1A20E08	—	—
	220	3PS1WA+1A20E03	3PS1WA+1A30E03	3PS1WA+1A3NE03
	380	A1811	A1825	A1812
	660	—	3PS1WA+1A30E19	3PS1WA+1A3NE19
	250DC	3PS1WA+1A20E20	—	—
32	24	3PS3WA+3A20E08	—	—
	220	3PS3WA+3A20E03	3PS3WA+3A30E03	3PS3WA+3ANE03
	380	A1816	A1817	A1804
	660	—	3PS3WA+3A30E19	3PS3WA+3A3NE19
	250DC	3PS3WA+3A20E20	—	—
63	24	3PS6WA+6A20E08	—	—
	220	3PS6WA+6A20E03	3PS6WA+6A30E03	3PS6WA+6A3NE03
	380	A1803	A1818	A1985
	660	—	3PS6WA+6A30E19	3PS6WA+6A3NE19
	250DC	3PS6WA+6A20E20	—	—
125	24	3PS9WA+9A20E08	—	—
	220	3PS9WA+9A20E03	3PS9WA+9A30E03	3PS9WA+9A3NE03
	380	3PS9WA+9A20E01	A1819	A1820
	660	—	3PS9WA+9A30E19	3PS9WA+9A3NE19
	250DC	3PS9WA+9A20E20	—	—
200	24	3PS2WA+2A20E08	—	—
	220	3PS2WA+2A20E03	3PS2WA+2A30E03	3PS2WA+2A3NE03
	380	3PS2WA+2A20E01	3PS2WA+2A30E01	A1815
	660	—	A1814	3PS2WA+2A3NE19
	250DC	3PS2WA+2A20E20	—	—

AMPS	A	B	C	d	E	E1	F	kg	Cable entry
									ISO
16	110	101	82	6,5	70	70	82	0,22	M20x1,5
32	130	126	89	6,5	77	88	100	0,36	M25x1,5
63	170	158	105	7,5	89	112	128	0,64	M40x1,5
125	260	360	250	10	210	260	295	-	M50X1,5
200	270	340	250	10	210	260	295	-	M63X1,5

DIMENSIONS: IN mm



IP67   WATERTIGHT, DISCONNECTOR PANEL MOUNT APPLIANCE INLET - MOULDED

A	V	⊕ 2P+E	⊕ 3P+E	⊕ 3P+N+E
16	24	3PS1A20E08	—	—
	220	3PS1A20E03	3PS1A30E03	3PS1A3NE03
	380	A2730	A2731	A2732
	660	—	3PS1A30E19	3PS1A3NE19
	250DC	3PS1A20E20	—	—
32	24	3PS3A20E08	—	—
	220	3PS3A20E03	3PS3A30E03	3PS3A3NE03
	380	A2735	A2736	A2737
	660	—	3PS3A30E19	3PS3A3NE19
	250DC	3PS3A20E20	—	—
63	24	3PS6A20E08	—	—
	220	3PS6A20E03	3PS6A30E03	3PS6A3NE03
	380	A2738	A2739	A2740
	660	—	3PS6A30E19	3PS6A3NE19
	250DC	3PS6A20E20	—	—
125	24	3PS9A20E08	—	—
	220	3PS9A20E03	3PS9A30E03	3PS9A3NE03
	380	3PS9A20E01	A2741	A2742
	660	—	3PS9A30E19	3PS9A3NE19
	250DC	3PS9A20E20	—	—
200	24	3PS2A20E08	—	—
	220	3PS2A20E03	3PS2A30E03	3PS2A3NE03
	380	3PS2A20E01	3PS2A30E01	A2734
	660	—	A2733	3PS2A3NE19
	250DC	3PS2A20E20	—	—

Note: Disconnectors are also available with 2 additional pilot contacts (max 16A). Other voltages as per schedule are also available. All "A" numbers represent ex stock items. All other numbers are available on request.

AMPS	A	B	C	D	d	E	kg
16	47	15	57	66	5	48	0,24
32	52	19	67	77	5	55	0,38
63	60	28	80	91	5,5	66	0,64
125	75	27	100	113	6	81	1,5
200	85	38	100	130	6	99	2,4

DIMENSIONS: IN mm

