

|                        |  |
|------------------------|--|
| article#               | <b>A023-6x</b>   |
| article description    | <b>CEE-plug 32A 3p 6h SHARK black</b>  |
| description long       | CEE-plug 32A 3p 6h IP44/IP54 SHARK black<br>housing material: PA6<br>rated current: 32A<br>number of poles: 3 (2P+PE)<br>clock-position: 6h<br>rated voltage/frequency: 200-250V~ / 50+60Hz<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399214561  |
| country of origin      | AT   |
| customs number         | 85366990   |
| net weight             | 0,178 kg   |
| packaging quantity     | 10   |
| minimum order quantity | 10   |

|                                 |                       |
|---------------------------------|-----------------------|
| ETIM 9.0                        | EC000140              |
| IEC-amperage                    | 32 A                  |
| Number of poles                 | 3                     |
| Voltage according to EN 60309-2 | 230 V (50+60 Hz) blue |
| Clock hour position             | 6 h                   |
| Identification colour           | Blue                  |
| RAL-number                      | 9005                  |
| Degree of protection (IP)       | IP44                  |
| Connection system               | Screwed terminal      |
| Cable entry                     | Gland nut             |
| Angle of plug                   | Straight              |
| Material                        | Plastic               |
| Contact material                | CuZn                  |
| Surface treatment contacts      | Untreated             |

|                        |                       |
|------------------------|-----------------------|
| a                      | 150 mm                |
| b                      | 104 mm                |
| c                      | 63 mm                 |
| K (cable Ø)            | 11,5-20 mm            |
| SW                     | 50 mm                 |
| wire flexible          | 2,5-6 mm <sup>2</sup> |
| contact screws         | 110 Ncm               |
| strain relief          | 600 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 12-14 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |

