

AMPCO Data Sheet

| | |
|------------------------|--|
| article# | A0331-9 |
| article description | CEE-plug 63A 3p 9h IP44 POWER TWIST |
| description long | CEE-plug 63A 3p 9h IP44 POWER TWIST housing material: PA6 rated current: 63A number of poles: 3 (2P+PE) clock-position: 9h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass nickel plated, with pilot pin connection technology: frame terminals with screws IP protection class: IP44 |
| GTIN (EAN) | 9003399422072 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.534 kg |
| packaging quantity | 2 |
| minimum order quantity | 2 |

| | |
|---------------------------------|--------------------------|
| ETIM 9.0 | EC000140 |
| IEC-amperage | 63 A |
| Number of poles | 3 |
| Voltage according to EN 60309-2 | 380-415 V (50+60 Hz) red |
| Clock hour position | 9 h |
| Identification colour | Red |
| RAL-number | 7046 |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Angle of plug | Straight |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|----------------------|
| a | 250 mm |
| b | 102 mm |
| c | 184 mm |
| K (cable Ø) | 14,5-36 mm |
| SW | 61 mm |
| wire flexible | 6-16 mm ² |
| contact screws | 200 Ncm |
| connecting screws | 200 Ncm |
| strain relief | 1500 Ncm |
| dismantling length | 100 mm |
| stripping length | 15-18 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

