

article#	A6023-9
article description	CEE-switched interlocked socket compact 32A 3p 9h IP44/IP54
description long	CEE-switched interlocked socket compact 32A 3p 9h IP44/IP54 housing material: PA6 rated current: 32A number of poles: 3 (2P+PE) clock-position: 9h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals panel mounting, mechanical interlock switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA IP protection class: IP44/IP54
GTIN (EAN)	9003399474521
country of origin	AT
customs number	85366990
net weight	0,485 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC001324
IEC-amperage	32 A
Number of poles	3
Voltage according to EN 60309-2	380-415 V (50+60 Hz) red
Clock hour position	9 h
Identification colour	Red
Degree of protection (IP)	IP54
Switch	Mechanical locking
Material housing	Plastic
Model	Top cover
Contact material	CuZn
Surface treatment contacts	Nickel-plated

a	66 mm
wire flexible	2,5-6 mm ²
wire solid	2,5-10 mm ²
contact screws	120 Ncm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

