

| | |
|------------------------|---|
| article# | A8217-9v |
| article description | CEE-angled connector 16A 7p 9h IP44/IP54 |
| description long | CEE-angled connector 16A 7p 9h IP44/IP54 housing material: PC/ABS rated current: 16A number of poles: 7 (6P+PE) clock-position: 9h rated voltage/frequency: 220-250V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals IP protection class: IP44/IP54 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantity | 10 |
| minimum order quantity | 10 |

| | |
|---------------------------------|---------------------------|
| ETIM 9.0 | EC001320 |
| IEC-amperage | 16 A |
| Number of poles | 7 |
| Voltage according to EN 60309-2 | 200-250 V (50+60 Hz) blue |
| Clock hour position | 9 h |
| Identification colour | Blue |
| Degree of protection (IP) | IP54 |
| Connection system | Screwed terminal |
| Angle of plug | Angled |
| Cable entry | Gland nut |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|-----------------------|
| a | 118 mm |
| b | 89 mm |
| c | 119 mm |
| d | 20 ° |
| K (cable Ø) | 8-16 mm |
| SW | 42 mm |
| wire flexible | 1-2,5 mm ² |
| contact screws | 100 Ncm |
| strain relief | 500 Ncm |
| dismantling length | 50 mm |
| stripping length | 10-12 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

