



















Series	S-A 10A 230V/400V 4kV 3 			
No. of poles	3p + ⊕	3p + ⊕	4p + ⊕	4p + ⊕
Electrical characteristics according to EN61984 UL/CSA 600V-UL1977				
Color	Grey	Black	Grey	Black
Size	3A «21x21»	3A «21x21»	3A «21x21»	3A «21x21»
Terminal	Screw	Screw	Screw	Screw
Wire section mm ² /AWG	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14
Numbering	1-3	1-3	1-4	1-4
Female insert	7203.6001.0 A1338	7203.6001.1	7204.6002.0 A1373	7204.6002.1
Male insert	7203.6101.0 A1341	7203.6101.1	7204.6102.0 A1382	7204.6102.1
Series	S-A 16A 250V 4kV 3 			
No. of poles	10p + ⊕	10p + ⊕	16p + ⊕	16p + ⊕
Electrical characteristics according to EN61984 UL/CSA 600V-UL1977 Euromap				
Size	10A «49x16»	10A «49x16»	16A «66x16»	16A «66x16»
Terminal	Screw	Crimp	Screw	Crimp
Wire section mm ² /AWG	0,5÷2,5 / 20-14	0,14÷4 / 26-12	0,5÷2,5 / 20-14	0,14÷4 / 26-12
Numbering	1-10	1-10	1-16	1-16
Female insert	7210.4401.0 A1393	7210.4451.0	7216.4402.0 A1296	7216.4452.0
Male insert	7210.4411.0 A1392	7210.4461.0	7216.4412.0 A1381	7216.4462.0
Series	S-A 16A 250V 4kV 3 			
No. of poles	32p + ⊕		32p + ⊕	
Electrical characteristics according to EN61984 UL/CSA 600V-UL1977 Euromap				
Size	32A «66x40»		32A «66x40»	
Terminal	Screw		Crimp	
Wire section mm ² /AWG	0,5÷2,5 / 20-14		0,14÷4 / 26-12	
Numbering	1-16	17-32	1-16	17-32
Female insert	7216.4402.0 A1296	7216.4403.0 A1378	7216.4452.0	7216.4453.0
Male insert	7216.4412.0 A1381	7216.4413.0 A1388	7216.4462.0	7216.4463.0
Series	S-E 16A 500V 6kV 3 			
No. of poles	6p + ⊕	10p + ⊕	16p + ⊕	24p + ⊕
Electrical characteristics according to EN61984 UL/CSA 600V-UL1977				
Size	6B «44x27»	10B «57x27»	16B «77x27»	24B «104x27»
Terminal	Screw	Screw	Screw	Screw
Wire section mm ² /AWG	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14	0,5÷2,5 / 20-14
Numbering	1-6	1-10	1-16	1-24
Female insert	7306.6003.0 A1307	7310.6004.0 A1309	7316.6005.0 A1310	7324.6007.0 A1311
Male insert	7306.6103.0 A1300	7310.6104.0 A1302	7316.6105.0 A1303	7324.6107.0 A1304

