

Event Technology MIDNIGHT-SERIES

230V~		400V~					
50/60Hz 3p=6h 4p+5p=9h		50/60Hz 3p=9h 4p+5p=6h					
Cat.No.	Cat.No.	AMP	POLES	IP	Technical Pg.*		
A2135-6x		16	3	44	53-A	Coupler	
	A2145-6x	16	4	44	53-A		
	A2155-6x	16	5	44	53-A		
A2235-6x		32	3	44	53-A		
	A2245-6x	32	4	44	53-A		
	A2255-6x	32	5	44	53-A		
A2335-6xs		63	3	66/67	53-B	Coupler Includes "Pilot Contact"	
	A2345-6xs	63	4	66/67	53-B		
	A2355-6xs	63	5	66/67	53-B		
A2435-6xs		125	3	66/67	53-B		
	A2445-6xs	125	4	66/67	53-B		
	A2455-6xs	125	5	66/67	53-B		
A313-6x		16	3	44	53-C	Flanged Inlet Straight	
	A314-6x	16	4	44	53-C		
	A315-6x	16	5	44	53-C		
A323-6x		32	3	44	53-C		
	A324-6x	32	4	44	53-C		
	A325-6x	32	5	44	53-C		

with flange 70 x 70 - fixing center 56 x 56



TEC